

**Product: Regalia Exterior Emulsion**

Regalia Exterior Emulsion is a 100% Acrylic Emulsion Paints which gives superior durability to the exterior masonry walls from rigors of tropical climate. Its enriched acrylic based formulation provides smooth finish and dust and water-resistant properties to the surface



**Product Features:**

**Pack size**



**Colours Available**



More than 1000 shades

**Coverage**

140-160 sqft/L/coat

77 – 88 sqft/L/2 coats

**Pre-Painting Steps:**

**Cleaning**



**New Plastered surfaces** should be allowed to cure for at least 3 months prior to painting.

**Old Surface / Previously painted surface** - Clean thoroughly with wire-brush to remove loose/flaky material, grease, and dirt. Ensure that the surface is free from fungus, algae and moisture. In case of organic growths like fungus, remove them with mild solution of household bleaching powder (recommended proportion 2kg to 50 Lts water), and leave it for 24 hours and then wash the surface again with clean water. Rectify and smoothen minor cracks and uneven surface with WALLPLUS Putty followed by two coats of WALLPLUS Water Primer. Fill the bigger cracks using cement & sand mixture in the ratio of 2:3.

**Filling cracks**



Extra care should be taken for surface like sunshades, parapets, and other horizontal surface where water accumulates during rains.

**Application Procedure:**

Stir the mixer properly before use. Use a good quality paint brush, roller, or spray gun for painting. Avoid under thinning or over thinning of paint. Apply two coats of WALLPLUS water primer. Mix three parts of clean water with four parts of paint by volume and apply 2-3 coats of it. For Horizontal Surfaces - Like top of windows, hedges, sunshades, and parapets etc. where water accumulates during rains should be painted with three and more coats for greater protection. The recoating time between two coats should be minimum four to six hours.

**Recommended tools for application:**



**Technical Details:**

- > Drying Time (touch dry): 30 minutes
- > Finish: Matt
- > Sheen level: 7 to 10 GU at 60°
- > Stability of thinned paint: To be used within 24 hours.
- > Washability: Best in class
- > Shelf Life: 60 months

**PRECAUTIONS:**

- > Please refer to MSDS doc of the paint for information on safety measures while handling the paint.
- > Keep out of the reach of children.
- > Store the container with the lid tightly closed and in upright position in a cool and dry position.