

## Umang Interior Emulsion

Umang Interior Emulsion is an economy interior emulsion that gives cost effective solution to your interior wall painting.



### Product Features:

#### Pack size



#### Colours Available



More than 1000 shades

#### Coverage

44 – 50 Sq.Ft/L/2 coats

### Pre-Painting Steps:

#### Cleaning



#### Filling cracks



**New Plastered surfaces:** It should be allowed to cure for at least 3 months prior to painting.

**Old Surface / Previously painted surface:** Clean thoroughly with wire-brush to remove loose/flaky material, grease, and dirt. Ensure that the surface is free from fungus, algae and moisture. Rectify and smoothen minor cracks and uneven surface with WALLPLUS Putty followed by two coats of WALLPLUS Water Primer. Fill the bigger cracks using cement & sand mixture in the ratio of 2:3 before application of putty.

### Application Procedure:

Mix 3 part of LUXORE INTERIOR EMULSION with 1 part of clean water by volume. Avoid under thinning or over thinning of paint. Stir the mixed paint properly before use. Use a good quality paint brush, roller, or spray gun for painting. Apply minimum two coats of Luxore Interior emulsion in a time gap of 4 to 6 hrs. between each coat. After taking out the required quantity the lid of the container must be closed tightly and avoid direct contact of bare hand.

#### Recommended tools for application:



Brush



Roller



Spray

### Technical Details:

- > Drying Time (touch dry): 30 minutes
- > Finish: Matte
- > Sheen level: 1 to 3 GU at 60°
- > Stability of thinned paint: To be used within 24 hours.
- > Washability: Medium
- > Shelf Life: 18 months

### Precautions:

- > Please refer to MSDS of the paint for information on safety measures while handling the paint.
- > Keep out of the reach of children.
- > Store the container with the lid tightly closed and in upright position in a cool and dry place.