



**THE TATA PIGMENTS LTD**  
**(An ISO 9001- 2015 certified company)**  
Sakchi Boulevard, Jamshedpur 831002

**TECHNICAL DATA SHEET OF ECOCEM CEMENT PAINT**

Tata Pigments Ecocem is a water proof cement paint to give extra protection to buildings in different weather conditions. This provides a hard, durable coating which resists penetration of moisture and does not rub, flake or peel off from the surface.

**PERFORMANCE FEATURES**

Tata Pigments Cemplus cement paint has good opacity. It has good opacity. It has anti fungal and anti algal properties which makes it a long lasting paint. It can be directly applied over porous surfaces of masonry, concrete, common bricks and rough plastics. This can be used for internal as well as external surfaces for a hygenic, water proof and decorative finish.

**SURFACE PREPERATION**

The surface to be painted must be free from all dust, grease, traces of paint flakes, fungus,etc. the surface previously coated with paint must be cleaned thoroughly with a stiff coir brush, to remove dust, dirt chalking or any friable material. This ensures proper adhesion of new paint system. All structural cracks must be open in V shape filled with white cement/cement based plasters. All leakages should be stopped before actual painting. Freshly plastered surface must be allowed to cure completely.

**COLOUR PROPERTIES**

High performance colour pigments that offer excellent matt finish to the wall and can be applied on all types of surfaces.

**CURING PROPERTIES**

2 - 3 times curing after first coat within next 8-16hrs. Apply 2<sup>nd</sup> coat after 8-16 hrs and then again 2 – 3 times curing.

**RECOMMENDED SYSTEM FOR APPLICATION**



**DRYING PROPERTIES**

Surface dry within 8 hrs \*

Overcoating time( @27±2 0C & RH= 60 ± 5) : 14-16 hrs \*

**SHEEN LEVELS**

Matt Finish



**THE TATA PIGMENTS LTD**  
**(An ISO 9001- 2015 certified company)**  
Sakchi Boulevard, Jamshedpur 831002

**THINNING PROPERTIES**

1kg cemplus thinned with 1000ml of water

**FLASH POINT**

IS :101/1987 part 1, section 6 – Not Applicable

**STABILITY OF THINNED PAINT**

To be used within 1.5 hours (Under Standard condition)

**OPACITY**

Provides good opacity to the surface, protecting it against all damages.

**COVERAGE**

15 - 20 sq ft/kg/2coats, on normal masonry surface by brush application.\*\*

**SHADE RANGE**

All the shades available in the Ecocem shade card.

**PRECAUTIONS**

- Do not apply when ambient temperature is less than 10°C or if the temperature might drop to this level within 4 hrs of application
- Do not over-thin or over-extend the brush
- Do not paint when it is raining
- Do not use saline water for sprinkling
- Avoid application of paint under strong direct sun as it may cause fast drying, brush marks and even patchy surfaces
- If the surface is too absorbent then the first coat may have to be applied with more than usual thinning

**NOTE:-**

**\*\*Actual coverage may vary depending on the surface porosity, surface roughness, temperature and application technique.**

**\* Drying time is checked @27±2 °C & RH= 60 ± 5**

*Mohua Ghoshabalan*

**Ast Manager (R&D)**